



2023 Collegiate Design Series
SAE Aero Design Rules



Version 2023.0

Forward

Welcome to SAE Aero Design 2023! Our mission is to provide students with real-world engineering experience through aircraft design challenges.

This year we refresh the rules for Regular Class. After iterations including tennis balls as passengers to simulate airlines, and soccer balls to simulate large cargo, we are going back towards the basics. Regular class is now focused on structural efficiency with heavy lift. Can you minimize your empty weight to maximize your total payload without sacrificing structural integrity? We cannot wait to see what teams develop, and expect the competition to be similarly exciting. These aircraft are set to be a bit bigger than we have had in a few years, so when off the flight line and/or in the pit area, teams will be required to remove their outer wing panels to make movement easier on everyone. Reassembly for flight will happen in the on-deck area before moving onto the flight line.

Last year saw Advanced Class change and become significantly more challenging, pushing teams to think and work at a systems level, and build capabilities over multiple years. These rules and scoring have been adjusted based on feedback to allow teams to get partial credit for demonstrating partial performance. The manual PADA landing option has been removed as a result.

Starting at the 2020 competition we introduced and have iterated on 'roundless' flight operations and received very positive feedback, especially paired with taking the top 3 flights for a team's score. We will continue refining this idea with the goal of increasing the number of flights during the competition and maximizing each team's opportunity to fly.

The next operation we will be refining is technical inspection. Since moving to the virtual presentations and holding tech inspection at the field, we have seen that very few teams are making it through on their first try, and only a fraction pass on Friday. To address this, we have split inspection into Safety and Compliance. All items on the safety list will be checked, but teams will sign off on the requirement compliance items themselves and a smaller number of those will be checked. Any compliance item that is signed off but not within spec will result in a points loss. Teams will no longer fill out ECRs. To help, we will be filming videos and providing documentation for what each inspection item is, how we will measure each, and the tolerance we will hold to. These resources will help teams at all experience levels come to the competition prepared for the inspection process.

Please read this document closely as there are changes to almost every section that even experienced teams will need to pay attention to. Please watch the website and SAE Aero Design App for announcements on operations and follow-up resources like videos and checklists. Finally, please make use of the Aero Design question and answer forum to resolve questions.

Everyone at SAE Aero Design wishes all teams the best of luck for Aero Design 2023!

- SAE Aero Design Rules Committee

TABLE OF CONTENTS

1	Competition Requirements	8
1.1	Introduction.....	8
1.2	SAE Aero Design Rules and Organizer Authority	8
	Penalties.....	8
	Rules Authority.....	8
	Rules Validity.....	9
	Rules Compliance.....	9
	Understanding the Rules.....	9
	Loopholes.....	9
	Participating in the Competition	9
	Visa--United States Visas.....	9
	Letters of Invitation.....	10
	Certificates of Participation.....	10
	Violations of Intent.....	10
	Right to Impound	10
1.3	Society Membership and Eligibility.....	10
	Society Membership	10
	Team Pilots.....	10
1.4	Liability Waiver and Insurance Requirements	11
1.5	Ringers Prohibited	11
1.6	Design and Fabrication	11
1.7	Original Design.....	11
1.8	Official Languages.....	11
1.9	Unique Designs	11
1.10	Aircraft Classification/Duplicate Aircraft	12
	1. One Team Entry per Class.....	12
	2. Backup Aircraft	12
1.11	Airframe Eligibility.....	12
1.12	Registration Information, Deadlines and Waitlist.....	12
	Team/Class/University Policy	12
	Individual Registration Requirements – ACTION REQUIRED.....	12
	Pre-Registration Information	13
1.13	Waitlist.....	13
1.14	Policy Deadline	14
	Failure to meet deadlines	14

Late Submission Penalty	14
Automatic Withdrawal Policy.....	14
1.15 Faculty Advisor	14
1.16 Questions, Complaints and Appeals	15
Questions	15
Complaints	15
Appeal / Preliminary Review	15
Cause for Appeal	15
Appeal Format	15
Appeals Period	16
Appeals Committee.....	16
1.17 Professional Conduct.....	16
Unsportsmanlike Conduct.....	16
Arguments with Officials.....	16
Alcohol and Illegal Material.....	16
Organizer’s Authority	16
Ground Safety and Flight Line Safety Equipment.....	17
1.18 SAE Technical Standards Access	17
2 General Aircraft Requirements	18
2.1 Aircraft Identification.....	18
2.2 Prohibited Aircraft Configuration	18
2.3 Empty CG Design Requirement and Empty CG Markings on Aircraft	18
2.4 Gross Weight Limit	19
2.5 Controllability	19
2.6 Radio Control System	19
2.7 Spinners or Safety Nuts Required.....	19
2.8 Metal Propellers	19
2.9 Lead is Prohibited	19
2.10 Payload Distribution	19
2.11 Static Payload Plate Attachment	19
2.12 Aircraft ballast	20
2.13 Control Surface Slop	20
2.14 Servo Sizing.....	20
2.15 Clevis Keepers.....	20
2.16 Stored Energy Restriction	20

2.17	Battery Pack Restrictions	20
2.18	Use of Lasers.....	20
2.19	Power Limiter	20
2.20	Red Arming Plug	21
2.21	Repairs, Alterations, and Spares.....	22
2.22	Alteration after First Flight	22
3	Mission Requirements and Scoring.....	23
3.1	Air Boss	23
3.2	Pilot Station(s)	23
3.3	Flight Attempt.....	23
3.4	Motor Run-Up Before Take-off.....	23
3.5	Aircraft Configuration at Liftoff and During the Flight Attempt	23
3.6	Competition Circuit Requirements	24
3.7	Time Limits and Multiple Flights Attempts.....	24
3.8	On-Deck Area.....	25
3.9	Take-off.....	25
3.10	Landing Requirements.....	26
3.11	Grounding an Aircraft	26
3.12	No-Fly Zone.....	26
3.13	Flight Rules Announcement.....	27
3.14	Flight Rules Violations.....	27
3.15	Local Field Rules.....	27
3.16	Competition Scoring	27
3.17	Aircraft Empty Weight Definition	27
4	Design Report.....	28
4.1	Submission Deadlines	28
4.2	Original Work.....	28
4.3	Technical Design Report Requirements.....	29
4.4	2D Drawing Requirements.....	30
	2D Format and Size	30
	Markings Required	30
	Views Required	30

	Dimensions Required	30
	Summary Data Required	31
4.5	Tech Data Sheet: Payload Prediction (Regular Class Only)	32
4.6	Tech Data Sheet: Powered Autonomous Delivery Aircraft (Advanced Class Only).....	33
4.7	Tech Data Sheet: Air-Systems Operations Plan	33
4.8	Tech Data Sheet: Aircraft Performance Prediction (Micro Class Only).....	33
5	Technical Presentation	34
5.1	Technical Presentation Requirements.....	34
5.2	Technical Presentation Process and Procedures	35
6	Requirements Check & Safety and Airworthiness Inspection	36
6.1	Aircraft Conformance to 2D drawing.....	36
6.2	Deviations from 2D drawing	36
6.3	Safety and airworthiness of aircraft.....	37
6.4	Inspection of spare aircraft and spare aircraft components	37
6.5	Aircraft must maintain Compliance throughout the competition.	37
6.6	Requirements Check & Safety and Airworthiness inspection penalties	37
7	Regular Class Design Requirements	38
7.1	Aircraft Dimension Requirement.....	38
7.2	Material and Equipment Restrictions for Regular Class	38
	Fiber-Reinforced Plastic (FRP).....	38
	Rubber bands.....	38
	Stability Assistance.....	38
7.3	Aircraft System Requirements	38
	Electric Motor Requirements.....	38
	Gear boxes, Drives, and Shafts.....	38
	Aircraft Propulsion System Battery	38
	Power Limiter.....	39
	Receiver System Battery and Switch.....	39
7.4	Payload Requirements.....	39
	Types of Cargo	39
	Cargo Bay Requirements.....	39
	Regular Boxed Cargo Support Requirements.....	39
7.5	Regular Class Payload Unloading	39
7.6	Regular Class Scoring.....	40
8	Advanced Class Design Requirements.....	41

8.1	Video documentation of proven operational ability for Advanced class.....	41
8.2	Aircraft Dimension Requirement.....	41
8.3	Aircraft System Requirements.....	41
	Electric Motor Requirements.....	41
	Gear boxes, Drives, and Shafts.....	41
	Aircraft Propulsion System Battery.....	41
	Power Limiter.....	41
8.4	Receiver System Battery.....	42
8.5	Rubber Bands.....	42
8.6	Primary Aircraft Static Payload Requirements.....	42
	Water Storage Container Requirements.....	42
	Static Payload Requirements.....	42
8.7	Powered Autonomous Delivery Aircraft (PADA) Requirements.....	42
8.8	Landing zones.....	43
8.9	Ground Transport Vehicle (GTV) Requirements.....	43
8.10	Gyroscopic and other stability augmentation.....	44
8.11	Autonomous flight.....	44
8.12	Frequency Request Procedure.....	44
8.13	Data Acquisition System (DAS).....	44
8.14	DAS Failures.....	45
8.15	First Person View System (FPV).....	45
8.16	Payload Specialist.....	45
8.17	Powered Autonomous Delivery Aircraft Release Procedures.....	46
8.18	Ground Transport Vehicle Demonstration Event Procedure.....	46
8.19	Advance Class Scoring.....	48
9	Micro Class Design Requirements.....	49
9.1	Aircraft Dimension Requirements.....	49
9.2	Aircraft Systems Requirements.....	49
	Propulsion Requirements.....	49
	Propeller and Gearbox.....	49
	Aircraft Propulsion System Battery.....	49
	Gyroscopic Assist Allowed.....	49
	Power Limiter.....	49
9.3	Payload requirements.....	49

Types of Cargo	49
Cargo Bay Requirements.....	49
Payload Plate Support Requirements	49
Delivery Box Definition.....	50
9.4 Payload Unloading.....	50
9.5 Micro Class Aircraft Launch	51
9.6 Mission Requirements	51
Aircraft Take-off and Circuit.....	51
9.7 Micro Class Flight Scoring.....	52
Appendix A - Statement of Compliance	53
Appendix B - Appeals.....	54
Appendix C – DAS, FPV, Radio Frequency Request Form	55

1 COMPETITION REQUIREMENTS

1.1 INTRODUCTION

Official Announcements and Competition Information

The SAE Aero Design competition is intended to provide undergraduate and graduate engineering students with a real-world design challenge. These rules were developed by industry professionals with a focus on educational value and hands-on experience. These rules were designed to compress a typical aircraft development program into one calendar year, following the early development phase of system engineering and requirements derivation. This competition will expose participants to the nuances of conceptual design, manufacturing, system integration/test, and verification through demonstration.

SAE Aero Design features three classes of competition—Regular, Advanced, and Micro.

1. **The Regular Class** is an all-electric class intended to develop a fundamental understanding of aircraft design.
2. **The Advanced Class** is an all-electric class designed to inspire future engineers to take a systems approach to problem solving, at the same time, exposing them to explore the possibilities of autonomous flights.
3. **The Micro Class** is an all-electric class designed to help students balance trades studies between multiple conflicting requirements. e.g. carrying the highest payload fraction possible, while simultaneously pursuing the lowest empty weight possible.

Other SAE Aero Design Competitions:

SAE BRASIL <http://www.saebrasil.org.br>

1.2 SAE AERO DESIGN RULES AND ORGANIZER AUTHORITY

General Authority

SAE International and the competition organizing bodies reserve the rights to revise the schedule of any competition and/or interpret or modify the competition rules at any time and in any manner, that is, in their sole judgment, required for the efficient and safe operation of the event or the SAE Aero Design series.

Penalties

SAE International and the competition organizing bodies reserve rights to modify the points and/or penalties listed in the various event descriptions; to accurately reflect the operations execution of the events, or any special conditions unique to the site.

Rules Authority

The SAE Aero Design Rules are the responsibility of the SAE Aero Design Rules Committee and are issued under the authority of the SAE Collegiate Design Series. Official announcements from the SAE Aero Design Rules Committee, SAE International or the other SAE International Organizers shall be considered part of and have the same validity as these rules. Ambiguities or questions concerning the

meaning or intent of these rules will be resolved by the officials, SAE International Rules Committee or SAE International Staff.

Rules Validity

The SAE Aero Design Rules posted at www.saeerodesign.com/go/downloads and dated for the calendar year of the competition are the rules in effect for the competition. Rule sets dated for prior competition years are invalid.

Rules Compliance

By entering an SAE Aero Design competition, the team members, Faculty Advisors and other personnel of the entering university agree to comply with, and be bound by, the rules and all rules interpretations or procedures issued or announced by SAE International, the SAE Aero Design Rules Committee and other organizing bodies. All team members, Faculty Advisors and other university representatives are required to cooperate with and follow all instructions from Competition Organizers, officials, and judges.

Understanding the Rules

Teams are responsible for reading and understanding the rules in their entirety for the competition in which they are participating. The section and paragraph headings in these rules are provided to facilitate reading: they do not affect the paragraph contents.

Loopholes

It is virtually impossible to anticipate a comprehensive design space that covers all possibilities and potential questions about the aircraft's design parameters or the conduct of the competition. Please keep in mind that safety remains paramount during any SAE International competition, so any perceived loopholes should be resolved in the direction of increased safety/concept of the competition. When in doubt, please contact the SAE Aero Design Rules Committee, using the FAQ forum, early to avoid design impacts at competition.

Participating in the Competition

Teams, team members as individuals, Faculty Advisors and other representatives of a registered university who are present on-site at a competition are considered to be "participating in the competition" from the time they arrive at the event site until they depart the site at the conclusion of the competition or earlier by withdrawing.

Visa--United States Visas

Teams requiring visas to enter to the United States are advised to apply at least sixty (60) days prior to the competition. Although most visa applications seem to go through without an unreasonable delay, occasionally teams have had difficulties and, in several instances, visas were not issued before the competition.

AFFILIATED CDS STUDENT TEAM MEMBERS WILL HAVE THE ABILITY TO PRINT OUT A REGISTRATION CONFIRMATION LETTER FOR THE INDIVIDUAL EVENT(S) THAT THEY ARE ATTENDING. ONCE A STUDENT TEAM MEMBER AFFILIATES THEMSELVES TO THEIR TEAM PROFILE PAGE UNDER THEIR INDIVIDUAL EDIT SECTION, THEY WILL HAVE THE OPPORTUNITY TO PRINT OUT THEIR

PERSONALIZED LETTER WITH THE FOLLOWING INFORMATION: STUDENT'S NAME, SCHOOL'S NAME, THE CDS EVENT NAME, OFFICIAL DATES AND LOCATION(S).

Letters of Invitation

Neither SAE International staff nor any Competition Organizers are permitted to give advice on visas, customs regulations or vehicle shipping regulations concerning the United States or any other country.

Certificates of Participation

SAE International and Competition Organizers do not create any Participation Certificates outside of the auto-generated certificate on your team profile page at sae.org.

Certificates are available as soon as students are affiliated to the current competition's team. Certificates will not be available once that competition year closes.

Violations of Intent

The violation of the intent of a rule will be considered a violation of the rule itself. Questions about the intent or meaning of a rule may be addressed to the SAE International Officials, Competition Organizers or SAE International Staff.

Right to Impound

SAE International and the other competition organizing bodies reserve the right to impound any on-site vehicle/aircraft at any time during a competition for inspection and examination by the Competition Organizers, officials, and technical inspectors.

1.3 SOCIETY MEMBERSHIP AND ELIGIBILITY

Society Membership

Individual team members must be members of SAE International or an SAE International affiliate society. Proof of membership, such as a membership card, is required at the event. Students may join online at:

<https://www.sae.org/participate/membership/join>

Teams are also required to read the articles posted on the SAE Aero Design News Feed (www.sae.org/aerodesign.com/go/news) published by SAE International and the other organizing bodies. Teams must also be familiar with all official announcements concerning the competition and rule interpretations released by the SAE Aero Design Rules Committee.

Team Pilots

Team pilots are not required to be students or SAE International members; however, all pilots must be current members of the Academy of Model Aeronautics or the Model Aircraft Association of Canada (AMA has an agreement with MAAC). Valid AMA membership cards must be presented at the flying field prior to flying any team's aircraft. Non-US pilots can obtain a discounted AMA Affiliate membership that covers flying activities while in the US by going to the AMA web site and submitting the following form: <https://www.modelaircraft.org/files/902.pdf>.

1.4 LIABILITY WAIVER AND INSURANCE REQUIREMENTS

All on-site participants and Faculty Advisors are required to sign a liability waiver which is part of their Fast-Track Registration Form that can be printed off their team registration page. Individual medical and accident insurance coverage is the sole responsibility of the participant.

1.5 RINGERS PROHIBITED

In order to maintain the integrity of the competition, the Faculty Advisor must prohibit ringers. A ringer is someone that has exceptional skills related to the competition (e.g., a professional model builder) that cannot be a legal member of the team but helps the team win points.

1.6 DESIGN AND FABRICATION

The aircraft must be designed and built by the SAE International student members without direct involvement from professional engineers, radio control model experts, pilots, machinists, or related professionals. The students may use any literature or knowledge related to R/C aircraft design and construction and information from professionals or from professors, as long as the information is given as discussion of alternatives with their pros and cons and is acknowledged in the references in the design report. Professionals may not make design decisions, nor contribute to the drawings, the report, or the construction of the aircraft. The Faculty Advisor must sign the Statement of Compliance given in the Appendix.

1.7 ORIGINAL DESIGN

Any aircraft presented for competition must be an original design whose configuration is conceived by the student team members. Photographic scaling of an existing model aircraft design is not allowed. Use of major components such as wings, fuselage, or empennage of existing model aircraft kits is prohibited. Use of standard model aircraft hardware such as motor mounts, control horns, and landing gear is allowed.

1.8 OFFICIAL LANGUAGES

The official language of the SAE Aero Design series is English. Document submissions, presentations and discussions in English are acceptable at all competitions in the series.

Team members, judges and officials at Non-U.S. competition events may use their respective national languages for document submissions, presentations and discussions if all the parties involved agree to the use of that language.

1.9 UNIQUE DESIGNS

Universities may enter more than one team in each SAE Aero Design competition, but each entry must be a unique design, significantly different from each other. If the aircraft are not significantly different in the opinion of the Rules Committee and Organizer, then the university will be considered to have only a single entry and only one of the teams and its aircraft will be allowed to participate in the competition. For example, two aircraft with identical wings and fuselages but different empennage would likely not be considered significantly different. For guidance regarding this topic, please submit a rules question at www.saeaerodesign.com.

1.10 AIRCRAFT CLASSIFICATION/DUPLICATE AIRCRAFT

1. One Team Entry per Class

A university is limited to registering one team per class.

2. Backup Aircraft

When a team has an identical aircraft as a back-up, the back-up aircraft must go through inspection with the primary aircraft.

1.11 AIRFRAME ELIGIBILITY

Airframes will only be allowed to compete during a single academic year. An airframe may be entered in both SAE Aero Design East and SAE Aero Design West during the same calendar year, but that same airframe may not be used in either competition during the following year. Entering the same airframe in SAE Aero Design West one year and SAE Aero Design East the next year is not allowed.

An airframe is considered entered to competition during an academic year once documentation on the design is submitted. If the airframe does not fly at competition during that same academic year, the airframe is not eligible for competition during future academic years.

The airframe must have been designed within eleven (11) months of competition and constructed within nine (9) months of competition. The airframe is defined as the fuselage, wings, and tail.

1.12 REGISTRATION INFORMATION, DEADLINES AND WAITLIST

Teams intending to participate in the 2023 SAE Aero Design competitions must register their teams online per the open registration schedule shown in Table 1.1.

Table 1.1 Open Registration Schedule

Event	Start (Open)	End (Closed)
<i>Registration Window</i>	September 20, 2022 10:00 AM EDT	December 1, 2022 11:59 PM EST

The registration fee is non-refundable and failure to meet these deadlines will be considered a failure to qualify for the competition. Separate entry fees are required for the events.

Team/Class/University Policy

A university or college can only have one aircraft registered per class. A university cannot register more than one team per class. The registration fees indicated on the website must be paid within 48 hours of registration to be eligible.

Individual Registration Requirements – ACTION REQUIRED

A team member must be enrolled as degree seeking undergraduate or graduate student in the college or university of the team with which they are participating. Team members who have graduated during the seven-month period prior to the competition remain eligible to participate.

All participating team members and Faculty Advisors must be sure that they are individually affiliated to their respective school / university on the SAE International website (www.sae.org) Team Profile page.

If you are not an SAE International member, go to www.sae.org and select the “Membership” link. Students will need to select the “Student Membership” link and then follow the series of questions that are asked. Please note: all student participants must be members of one of the organizations listed in Section 1.3 to participate in the events.

Faculty members who wish to become SAE International members should choose the “Professional Membership” link. Please note: this is not mandatory for Faculty Advisors.

All student participants and Faculty Advisors must affiliate themselves to the appropriate team(s) online.

The “Add New Member” button will allow individuals to access this page and include the necessary credentials. If the individual is already affiliated to the team, simply select the Edit button next to the name. Please be sure this is done separately for each of the events your team has entered.

All students, both domestic and international, must affiliate themselves online prior to the competition.

Each team member may participate for only one team. If the university or college is entering multiple classes, team members must choose only one team to affiliate with and participate in the competition with. For example, students cannot compete as part of a Micro class team and an Advanced class team.

Pre-Registration Information

SAE will not be utilizing the pre-registration process for 2023. Teams who wish to participate should be prepared to register during the normal registration window.

****NOTE: When your team is registering for a competition, only the student or Faculty Advisor completing the registration needs to be linked to the school. All other students and faculty can affiliate themselves after registration has been completed; however, this must be completed no later than two weeks before the competition start date.**

1.13 WAITLIST

Once an event reaches the venue’s capacity, all remaining registered team(s) will be asked to be placed on a waitlist. The waitlist is capped at 40 available spaces per event and will close on the same day as registration closes. Once a team withdraws from an event, an SAE International Staff member will inform your team by email (the individual who registered the team to the waitlist) that a spot on the registered teams list has opened. You will have 24 hours to accept or reject the position and an additional 24 hours to have the registration payment completed or process for payment begun. Waitlisted teams are required to submit all documents by the deadlines to be considered serious participants and any team that does not submit all documents will be removed from the waitlist.

1.14 POLICY DEADLINE

Failure to meet deadlines

Teams registering for SAE Aero Design competitions are required to submit several documents prior to the competition including a Design Report and Technical Data Sheet that the event judges use to evaluate the team during the competition. When these documents are not submitted, judges cannot accurately assess the team. Additionally, teams that do not submit required documents typically do not come to the competition. Teams that do not notify us that they are withdrawing create the following problems:

- They are included in the static event schedules and judging time is wasted.
- Their unused registration slot cannot be offered to a team on the waitlist. Additionally, failure to submit the required documents is a clear violation of the rules.

Late Submission Penalty

Late submission or failure to submit the Design Report by the deadline will be penalized five (5) points per day. If your required documents are received more than five (5) days late, the documents will be classified as “Not Submitted” and your team will not be allowed to participate. Additionally, the automatic withdrawal policy will be in effect.

Automatic Withdrawal Policy

Failure to submit the required Design Report, Technical Data Sheet, and Drawings within five (5) days of the deadline will constitute an automatic withdrawal of your team. Your team will be notified before or on the 4th day of no submission that we have not received your documents and after the 5th day your team’s registration will be canceled, and no refund will be given.

Activity/Action	Class	East Event Deadline	West Event Deadline
Event Registration	All	12/1/2022 11:59 PM EST	12/1/2022 11:59 PM EST
Design Report Submission	All	Reference www.saeaerodesign.com	
Frequency Request	Advanced	2/15/2023	2/15/2023
Withdrawal Request	All	Reference www.saeaerodesign.com	

1.15 FACULTY ADVISOR

Each team is expected to have a Faculty Advisor appointed by the university. The Faculty Advisor is expected to accompany the team to the competition and will be considered by competition officials to be the official university representative. Faculty Advisors may advise their teams on general engineering and engineering project management theory but may not design any part of the vehicle nor directly participate in the development of any documentation or presentation. Additionally, Faculty Advisors may neither fabricate nor assemble any components nor assist in the preparation, maintenance, or testing of the vehicle. In brief, Faculty Advisors may not design, build, or repair any part of the aircraft. Faculty Advisors that are not eligible student team members may not participate in flight operations during competition weekend except as noted.

1.16 QUESTIONS, COMPLAINTS AND APPEALS

Questions

Any questions or comments about the rules should be brought to the attention of the Rules Committee by submitting a rules question at <https://www.saeerodesign.com>.

General information about hotels and other attractions in the area, as well as a schedule of events, will be posted on the SAE International website according to the competition in which you are competing: <https://www.sae.org/attend/student-events/>

Complaints

Competition officials will be available to listen to complaints regarding errors in scoring, interpretation, or application of the rules during the competition.

Competition officials will not be available to listen to complaints regarding the nature, validity, or efficacy of the rules themselves at the competition. In other words, the Organizer will not change the rulebook at the field, unless the safety of the competition requires updates.

Appeal / Preliminary Review

A team can only appeal issues related to scoring, judging, venue policies, and/or any official actions *regarding their own team*. Team Captain(s) and/or Faculty Advisor must bring the issue to the Organizer's or SAE International staff's attention for an informal preliminary review before filing an official appeal.

A team cannot file an appeal to cause harm to another team's standing and/or score.

Cause for Appeal

A team may appeal any rule interpretation, own-team scoring or official actions which the team feel has caused some actual, non-trivial, harm to own-team, or has had a substantive effect on their score.

Teams may not appeal rule interpretations or actions that have not caused the team any substantive damage.

Appeal Format

If a Faculty Advisor or Team Captain(s) feel that their issue regarding an official action or rules interpretation was not properly addressed by the **event officials**, the team may file a formal appeal to the action or rules interpretation with the Appeals Committee.

All appeals must be filed in writing (see Appendix D) to the Organizer by the Faculty Advisor or Team Captain(s) only.

All appeals will require the team to post twenty-five (25) points as collateral. If the appeal is successful and the action is reversed, the team **will not** forfeit the twenty-five (25) collateral points. If the appeal is overruled, the team will forfeit the twenty-five (25) collateral points.

All rulings issued by the Appeals Committee are final.

Appeals Period

All appeals must be submitted within thirty (30) minutes of the end of the flight or other competition event to which the appeal relates.

Appeals Committee

When a timely appeal is received, the committee will review the claims. All contentions or issues raised in the formal appeal will be addressed in a timely manner. The consideration in each review is whether the actions in dispute were just and in-line with the intent of the rules. Once the review is completed, a new order will be issued affirming, reversing, or modifying the original determination.

All rulings issued by the Appeals Committee are final.

The Appeals Committee must consist of a minimum of three members: the Organizer or delegate, SAE International representative, and either the Chief Steward, the Chief Judge, the Air Boss and/or Rules Committee member.

1.17 PROFESSIONAL CONDUCT

Unsportsmanlike Conduct

In the event of unsportsmanlike conduct by team members or a team's Faculty Advisor, the team will receive a warning from a Competition Official. A second violation will result in expulsion of the team from the competition and loss of any points earned in all aspects of the competition.

Arguments with Officials

Arguments with or disobedience toward any competition official may result in the team being eliminated from the competition. All members of the team may be immediately escorted from the grounds.

Alcohol and Illegal Material

Alcoholic beverages, illegal drugs, firearms, weapons, or illegal material of any type are not permitted on the event sites at any time during the competition. Any violations of this rule will result in the immediate expulsion of all members of the offending school, not just the team member(s) in violation. This rule applies to team members and Faculty Advisors. Any use of illegal drugs or any use of alcohol by an underage person must be reported to the local law enforcement authorities for prosecution.

Organizer's Authority

The Organizer reserves the exclusive right to revise the schedule of the competition and/or to interpret the competition rules at any time and in any manner required for efficient operation or safety of the competition.

Ground Safety and Flight Line Safety Equipment

- **No open toe shoes allowed.** All team participants, including Faculty Advisors and pilots, are required to wear CLOSED toe shoes during flight testing and during flight competition.
- **Smoking is prohibited.** Smoking is prohibited in all competition areas.
- **Personal Protective Equipment required.** All students involved in flight-line launch and recovery operations for all aircraft classes must wear safety glasses.
- **Only non-visible Class 1 eye-safe (EN/IEC 60825-1 2014) lasers are allowed.** Laser pointers are prohibited.

1.18 SAE TECHNICAL STANDARDS ACCESS

A cooperative program of SAE International's Education Board and Technical Standards Board is making some of SAE International's Technical Standards available to teams registered for any North American CDS competition at no cost. The Technical Standards referenced in the Collegiate Design Series rules, along with other standards with reference value, will be accessible online to registered teams, team members and Faculty Advisors.

2 GENERAL AIRCRAFT REQUIREMENTS

2.1 AIRCRAFT IDENTIFICATION

Team number as assigned by SAE International must be visible on both the top and bottom of the wing, and on both sides of the vertical stabilizer or other vertical surface.

1. Aircraft must be identified with the school name, mailing address, and email address either on the outside or the inside of the aircraft.
2. Team numbers on Regular aircraft shall be a minimum of **4** inches in height.
3. Team numbers on the Advanced Class primary aircraft shall be a minimum of **4** inches in height. Team numbers on the Advanced Class Powered Autonomous Delivery Aircraft (PADA) shall be a minimum of **2** inch in height.
4. Team numbers on Micro Class shall be a minimum of **2** inch in height.
5. The University name must be clearly displayed on the wings or fuselage.
6. The University initials may be substituted in lieu of the University name provided the initials are unique and recognizable.

The assigned aircraft numbers appear next to the school name on the “Registered Teams” page of the SAE Aero Design section of the Collegiate Design Series website at:

SAE Aero East: <https://www.sae.org/attend/student-events/sae-aero-design-east>

SAE Aero West: <https://www.sae.org/attend/student-events/sae-aero-design-west>

2.2 PROHIBITED AIRCRAFT CONFIGURATION

Competing designs are limited to fixed wing aircraft only. Lighter-than-air aircraft, rotary wing aircraft such as helicopters or auto-gyros and steerable parafoil aircraft are not allowed to compete.

2.3 EMPTY CG DESIGN REQUIREMENT AND EMPTY CG MARKINGS ON AIRCRAFT

All aircraft must meet the following Center of Gravity (CG) related requirements:

1. All aircraft must be flyable at their designated Empty CG position (no payload, ready to fly) on the submitted 2D aircraft drawing.
2. All aircraft must have the fuselage clearly marked on both sides with a classic CG symbol (Figure 2.1) that is a minimum of 0.5 inches in diameter centered at the Empty CG position +/-0.25 inches, per the submitted 2D drawings. (Wing type aircraft may place the two CG markings on the bottom of the wing.)
3. The Empty CG location will be verified during Safety and Airworthiness Inspection.
4. No empty weight flight is required.




Figure 2-1 – Center of Gravity Symbol

2.4 GROSS WEIGHT LIMIT

Aircraft gross take-off weight may not exceed fifty-five (55) pounds.

2.5 CONTROLLABILITY

- All aircraft must be controllable in flight.
- If an aircraft is equipped with a wheeled landing gear, the aircraft must have some form of ground steering mechanism for positive directional control during takeoffs and landings. Aircraft may not rely solely on aerodynamic control surfaces for ground steering.

2.6 RADIO CONTROL SYSTEM

The use of a 2.4 GHz radio control system is required for all aircraft. The 2.4 GHz radio control system must have a functional fail-safe system that will reduce the throttle to zero **immediately** if the radio signal is lost. Teams may have to reset the default on the fail-safe to meet this requirement.

2.7 SPINNERS OR SAFETY NUTS REQUIRED

All powered aircraft must utilize either a spinner or a rounded model aircraft type safety nut. Nylon-insert Lock-Nuts are prohibited. See Figure 2-2 for examples of acceptable hardware.



Figure 2-2 - Spinners and Safety Nut

2.8 METAL PROPELLERS

Metal propellers are not allowed.

2.9 LEAD IS PROHIBITED

The use of lead in any portion of aircraft (payload included) is strictly prohibited.

2.10 PAYLOAD DISTRIBUTION

The payload cannot contribute to the structural integrity of the airframe, meaning, the airframe must be able to fly without the payload installed.

2.11 STATIC PAYLOAD PLATE ATTACHMENT

All static payload plates must be secured with metal hardware that penetrates all payload plates. Payload plates must also be secured to the aircraft structure with metal hardware as a single mass inside the designated payload bay, as defined by each class.

2.12 AIRCRAFT BALLAST

Aircraft ballast is allowed. Ballast cannot be in the payload bay and must be properly secured.

2.13 CONTROL SURFACE SLOP

Aircraft control surfaces and linkages must not feature excessive slop. Sloppy control surfaces lead to reduced controllability in mild cases, or control surface flutter in severe cases.

2.14 SERVO SIZING

Analysis and/or testing must be described in the Design Report that demonstrates the servos are adequately sized to handle the expected aerodynamic loads during flight.

2.15 CLEVIS KEEPERS

All control clevises must have additional mechanical keepers to prevent accidental opening of the control clevis in flight.

2.16 STORED ENERGY RESTRICTION

Aircraft must be powered by the motor on board the aircraft. No other internal and/or external forms of stored potential energy are allowed, for example rubber bands or pressure vessels like CO2 cartridges.

2.17 BATTERY PACK RESTRICTIONS

- All Batteries must be commercially available. Homemade batteries are not allowed.
- All batteries in the aircraft must be positively secured so that they cannot move under normal flight loads.
- The battery bay or location in the aircraft must be free of any hardware or other protrusions that could penetrate the battery in the event of a crash.

2.18 USE OF LASERS

The use of lasers for marking/highlighting landing zones or directing the navigation of an aircraft to a landing zone is prohibited.

2.19 POWER LIMITER

All classes require the use of a third-party electronic device to limit the amount of power the propulsion system can use. The official supplier for this part is Neumotors.com. The supplier has agreed to ship worldwide to any team. The limiters are only available at the follow link:

<https://neumotors.cartloom.com/storefront/category/student-contests-sae-dbf>

- Repair and/or modifications to the limiter are prohibited.
- The limiter must be fully visible and easy to inspect.
- Only battery, receiver, Battery Eliminator Circuit (BEC), speed control, arming plug, and limiter are allowed within the power circuit.

2.20 RED ARMING PLUG

All electric powered aircraft MUST use a discrete and removable red arming plug to arm and disarm the aircraft propulsion system. This red arming plug must be integrated into the electrical circuit between the battery and the electronic speed controller (ESC).

1. The red arming plug must be located on the positive (**RED**) wire between the battery and the power limiter.
2. The red arming plug must be located as follows:
 - The arming plug must be past the opposite edge of the wing from the propeller.
 - On a tractor flying wing or delta, the arming plug must be within 2 inches of the wing control surface hinge line or on the trailing edge of the main body/fuselage.




Figure 2-3: Layout diagram of red arming plug on several example aircraft configurations.

3. The red arming plug must be located on the top near the centerline of the fuselage or wing and external to the aircraft surface.
4. The location of the red arming plug must be clearly visible.
5. The non-removable portion of the arming plug interface may not have more than one male lead.
6. Disconnecting wiring harnesses to arm and disarm a system will NOT be allowed.




Figure 2-4: Example diagram of propulsion system with Arming Plug and Power Limiter. Note, different classes may have additional requirements, or allow for alternative configurations.

2.21 REPAIRS, ALTERATIONS, AND SPARES

1. The original design of the aircraft as presented in the written and oral reports must be maintained as the baseline aircraft during the competition.
2. In the event of damage to the aircraft, the aircraft may be repaired provided such repairs do not drastically deviate from the original baseline design. All major repairs must undergo safety inspection before the aircraft is cleared for flight.

2.22 ALTERATION AFTER FIRST FLIGHT

Minor alterations are allowed after the first and subsequent flight attempts.

1. A penalty will be assessed ONLY if 2/3 of the ruling committee (Event Organizer, Head scoring judge and/or SAE staff judge) agree that there were significant modifications made from the baseline configuration.
2. If the ruling committee determines that the changes are a result of safety-of-flight, the changes will not incur penalty points.

3 MISSION REQUIREMENTS AND SCORING

3.1 AIR BOSS

The Air Boss is a qualified SAE event official or appointed volunteer that manages the flight line process. Their responsibilities include:

- 1 Ensure the safety of the flight line through maintaining an orderly and controlled runway.
- 2 Be the official of record for the success or failure of the aircraft's flight, including takeoff and landing.
- 3 Declare termination of flight at any time during the attempt.
- 4 Air Boss, or event organizers, may continue flight operations at their discretion in continuous winds up to 45 knots with gusts no greater than 65 knots.

3.2 PILOT STATION(S)

Pilot area will be defined at pre-competition meeting (Friday Night All-hands). All pilots must fly from designated area.

3.3 FLIGHT ATTEMPT

Teams are allowed one (1) flight per attempt. There is no fixed or guaranteed number of flights. The number of flights possible will depend on local conditions.

- **Regular and Advanced Classes:** Without violating other take-off restrictions, a team can have multiple attempts to become airborne within the team's prescribed time limit for each respective class identified in Table 3.1.
- **Micro Class:** only one launch attempt is allowed per flight attempt.

3.4 MOTOR RUN-UP BEFORE TAKE-OFF

For all competition classes the aircraft may be throttled-up/run-up for take-off, subject to the following conditions:

- One (1) team member is allowed to hold the aircraft in place prior to take-off roll.
- The aircraft holder may not push the aircraft on release.
- **Regular Class Only:** the main gear must remain on the take-off line prior to release.

3.5 AIRCRAFT CONFIGURATION AT LIFTOFF AND DURING THE FLIGHT ATTEMPT

The aircraft must remain intact during a flight attempt to receive full flight score. A flight attempt includes activities at the starting line, the take-off roll, take-off, flight, landing and recovery after landing.

A twenty-five percent (25%) deduction from the flight score will be assessed if any of the following items are observed to completely detach from the aircraft during a flight attempt.

- Stickers
- Tape
- Coverings

Except for a broken prop during landing, if any other components fall off the during a flight attempt, the flight will be disqualified.

3.6 COMPETITION CIRCUIT REQUIREMENTS

1. During departure and approach to landing, the pilot must not fly the aircraft in a pattern that will allow the aircraft to enter any of the no-fly zones.
2. No aerobatic maneuvers will be allowed at any time during the flight competition in any competition class. This includes but not limited to: loops, figure 8's, Immelmann, all types of rolling maneuvers and inverted flight.
3. Regular and Micro Class aircraft must successfully complete a minimum of one 360° circuit. See Table 3.2 for additional information.
4. Advanced Class has no specific flight pattern. (See Advanced Class rules for details concerning the releasable payload drop mission element.)

3.7 TIME LIMITS AND MULTIPLE FLIGHTS ATTEMPTS

- A team's flight ticket will be surrendered when an event official starts the timer for the class-specific time allotment.
- Multiple takeoff attempts per flight ticket are allowed within the class-specific time allotment as long as the aircraft has NOT become airborne during an aborted attempt. Refer to Table 3.1 for additional information regarding multiple takeoff attempts.
- If an airborne aircraft returns to the ground after being airborne and is beyond the take-off limits, the flight attempt will be disqualified.

Table 3.1: Flight Attempt Information

Class	Time Limit (sec)	Can make multiple take-off attempts on one ticket if:			Take-off Attempt is defined as the point at which:
		Still within the Time Limit	Bounce within required take-off distance	Bounce outside the required take-off distance	
Regular	90	Yes	Yes	No	The main wheels leave the starting line
Advanced	60*	Yes	Yes	No	The aircraft moves forward under its own power
Micro	60	No	No	No	Aircraft moves forward under its own power

*See On-Deck Area for timing of system startup and data connection

3.8 ON-DECK AREA

When a team will be the next up to fly, they will be positioned in an area near the flight line where they can prepare for their flight attempt.

- Teams can use the on-deck area to mount their propellers and do control surface checks.
- Advanced class will have three (3) minutes to turn on and connect their DAS and ground systems. The start of this time will be considered the start of the flight attempt.
- Teams should have enough reserve power for any expected delays.
- Teams will not be allowed to install their propulsion arming plugs. Motor runup and testing will not be allowed.

3.9 TAKE-OFF

Take-off direction will be determined at the discretion of the Air Boss. If possible, the take-off direction will face into the wind. Changes in wind direction, in light and variable winds, may affect the take-off direction throughout the day. SAE Aero Design reserves the right to change the take-off direction at any time for weather or safety reasons.

1. Regular and Advanced Class aircraft must remain on the runway during the take-off roll.
2. Micro Class must be launched in accordance with section 9.5 from the designated launch area.
3. Distance requirements are defined in Table 3.2.
4. Making the initial turn before passing the “distance from initial start before turn” requirement will disqualify that flight attempt.

Table 3.2: Take-off Information

Class	Take-Off Distance Limits	Distance from initial start before turn	Description
Regular	100 ft.	400 ft.	Aircraft must be airborne within the prescribed take-off distance.
Advanced	None	None	Aircraft will have the full use of the runway.
Micro	See Section 9.5	See Section 9.6	Team may use the entire launch area per attempt to get the aircraft airborne. Only one (1) launch release per flight attempt is allowed.

3.10 LANDING REQUIREMENTS

A successful landing is defined as a controlled return to the ground. Aircraft must remain inside the specified landing zone for each class. The airplane may leave the landing zone only if given permission by the Air Boss.

The landing zone is a pre-determined fixed area for each class for the purpose of returning a flying aircraft to the ground. See Table 3.3 for class requirements.

1. The landing zones will be visibly marked at the site prior to the start of competition.
2. It is the team and team pilot's responsibility to be aware of the class-specific landing zone dimensions at the event site.
3. Any aircraft that leaves their designated landing zone or the paved runway for any reason during landing are subject to a penalty of fifty percent (50%) of any points earned during the flight prior to landing.
4. Any flight where the aircraft does not make the initial touch down for landing inside the designated landing zone is disqualified.
5. Touch-and-go landings are not allowed and will be judged as a failed landing.
6. The criterion for being within the landing zone is that no supporting part of the aircraft that is touching the ground can be outside the landing zone. For example, a wing tip or fuselage can overhang the edge of the landing zone, as long as no supporting part of the aircraft is physically touching outside the landing zone.

Table 3.3: Landing Distance Limit

Class	Landing Distance Limits (ft.)	Description
Regular	400 ft.	Aircraft must land in the same direction as take-off and stop within the designated landing zone.
Advanced	Available Runway	
Micro	200 ft.	

3.11 GROUNDING AN AIRCRAFT

1. An aircraft will be grounded if it is deemed non-flight-worthy or not in compliance with class rules by any SAE official, event official or a designated technical/safety inspector.
2. Until the non-flight-worthy or out of compliance condition has been addressed and has been cleared by re-inspection, the aircraft will not be allowed to fly in the competition.

3.12 NO-FLY ZONE

Each competition will have venue-specific **no-fly zones**. The no-fly zones will be defined during the all-hands briefing at the event and during the pilot's briefings.

1. At no time will an aircraft enter the no-fly zones, whether under controlled flight or uncontrolled.

2. The first infraction for crossing into the no-fly zone will result in an invalidated flight attempt and zero points will be awarded for that flight.
3. A second infraction will result in disqualification from the entire event and loss of all points.
4. It is the team and team pilot's responsibility to be aware of the venue-specific no-fly zones and to comply with all venue specific rules.
5. If a team is unable to directionally control their aircraft and it is headed towards or is in a no-fly zone, the Judges and/or Air Boss may order the pilot to intentionally crash the aircraft to prevent it from endangering people or property. This safety directive must be followed immediately, if ordered by the officials.

3.13 FLIGHT RULES ANNOUNCEMENT

Flight rules will be explained before the flight competition begins during a pre-competition pilots' meeting.

3.14 FLIGHT RULES VIOLATIONS

1. Violation of any flight rule may result in the team being eliminated from the competition.
2. All members of an eliminated team may be escorted from the grounds.

3.15 LOCAL FIELD RULES

In addition to competition rules, the local flying club may have additional rules in place at the event flying field.

1. Club rules will be obeyed during the flight competition.
2. If club rules conflict with competition rules, it is the responsibility of the Team Captain(s) and/or Faculty Advisor to bring attention to the conflict and follow the appeals process to resolve the conflict.

3.16 COMPETITION SCORING

A team's final, overall score is composed of scores in the following categories:

1. Technical Design Report (Design, Written and Drawing)
2. Presentation
3. Flight Event
4. Penalties

Teams must participate in all 3 main categories to be included in the overall score. Passing Requirements Check & Safety and Airworthiness inspection counts as participating in the Flight Event.

3.17 AIRCRAFT EMPTY WEIGHT DEFINITION

All aircraft parts that are not payload, as defined in the relevant class's section, contribute to the empty aircraft weight, including, but not limited to: airframe, receiver, electronics, batteries, hardware, brackets, straps and other associated features.

4 DESIGN REPORT

The Design Report is the primary means in which a team conveys the story of how their aircraft is the most suited design to accomplish the intended mission. The Design Report should explain the team's thought processes and engineering philosophy that drove them to their conclusions.

Some topics that are important to cover are: selection of the overall vehicle configuration, wing planform design including airfoil selection, drag analysis including three-dimensional drag effects, aircraft stability and control, power plant performance including both static and dynamic thrust, and performance prediction. Other topics should be included as appropriate. See the SAE Aero Design Report Guidelines available at www.saeerodesign.com/go/downloads for additional comments, suggested topics, and a suggested outline. For more information regarding performance prediction, a white paper by Leland Nicolai is also available at <http://www.saeerodesign.com/go/downloads>

4.1 SUBMISSION DEADLINES

The Technical Design Report, 2D drawing, and supplemental Tech Data Sheet (TDS) must be electronically submitted to www.saeerodesign.com no later than the date indicated on the Action Deadlines given on the SAE International Website:

<https://www.sae.org/attend/student-events>

Neither the Organizer nor the SAE International is responsible for any lost or misdirected reports, drawings, or server routing delays. The SAE International will not receive any paper copies of the reports through regular mail or email outside of the emergency submissions email.

4.2 ORIGINAL WORK

The Technical Design Report shall be the team's original work for the current competition year. Resubmissions of **previous and current** year's design reports will not be accepted. Recitation of previous year's work is acceptable **if and only if** appropriately cited and credited to the original author(s). Plagiarism is a forbidden industry and academic practice. All references, quoted text, and reused images from any source shall have appropriate citation within the text and within the Technical Design Report's Table of References, providing credit to the original author and editor.

Reports may be checked against **previous and current** years submissions to determine if re-use, copying, or other elements of plagiarism are indicated.

For the purposes of the SAE International Aero Design Competition, plagiarism is defined as any of the following:

- 1 Use of information from textbooks, reports, or other published material without proper citation
- 2 Use of sections or work from previous SAE Aero Design competitions without proper citation

If plagiarism is detected in the written report, a team will be given 24 hours to make a case to SAE and the SAE Aero Design Rules Committee. If the report and/or case is found to be insufficient, the team will receive zero score for the report. The team will be allowed to compete in all remaining categories of the competition but will not be eligible for awards. SAE also reserves the right to notify the University of the situation.

If plagiarism is detected in the oral presentation, team will receive zero score for the presentation. The team will be allowed to compete in all remaining categories of the competition but will not be eligible for awards. SAE also reserves the right to notify the University of the situation.

The SAE Aero Design Rules Committee & SAE International has the sole discretion to determine whether plagiarism is indicated, and the above rules are enacted. The above rules may be implemented at any time before, during, or for up to six (6) months after the competition event.

4.3 TECHNICAL DESIGN REPORT REQUIREMENTS

Technical Design Report will be 50 points (pts) of the competition score as broken down in Table 4.3.1.

- The Technical Design Report shall not exceed thirty (30) pages, including the cover page, certificate of compliance, and 2D Drawing. If the design report exceeds thirty (30) pages, the judges will only score the first thirty (30) pages.
- The Technical Design Report shall include a Cover Page with Team Name, Team Number, and School Name and Team Member Names.
- The Technical Design Report shall include a Certificate of Compliance signed by hand by the team's Faculty Advisor.
- The Technical Design Report shall be typewritten and double-spaced. Tables, charts, and graphs are exempt from this. For single-spaced reports, only the first fifteen (15) pages will be scored by judges. All other content sections will receive a zero (0).
- The report font shall be 12 pt. proportional; or 10 char/in. non-proportional font.
- The report margins shall be: 1" Left, 0.5" right, 0.5" top, and 0.5" bottom.
- Each page, except the Cover Page, Certificate of Compliance, 2D Drawing and Technical Data Sheet shall include a page number.
- All report pages shall be ANSI A (8 1/2 x 11 inches) portrait-format.
- The Technical Design Report shall include a Table of Contents, Table of Figures, Table of Tables, Table of References and Table of Acronyms.
- The Technical Design Report shall be single-column text layout.
- The Technical Design Report shall include the Technical Data Sheet(s) (TDS) appropriate for the team's competition entrant class. The TDS must include the Team Name, School Name, and Team Number.

Table 4.3.1 Technical Design Report

Section	Page Count	Points		
		Regular	Advanced	Micro
Cover Page	1	40	40	40
Certificate of Compliance	1			
Design Report	27			
2D Drawing	1	5	5	5
Total Document	30	45	45	45
TDS: Payload Prediction	1	5	-	-
TDS: Powered Autonomous Delivery Aircraft 2D Drawing	1	-	2.5	-
TDS: Air-Systems Operations Plan	1	-	2.5	-
TDS: Vehicle Performance	1	-	-	5
Total		50 pts	50 pts	50 pts

4.4 2D DRAWING REQUIREMENTS

2D Format and Size

The 2D drawing must be one (1) ANSI B sized page (PDF) format (11 x 17 inches). For teams outside North America that cannot submit an ANSI B size drawing, page format size must be the closest size available to ANSI B.

Markings Required

The 2D drawing must be clearly marked with:

1. Team Number
2. Team Name
3. School Name

Views Required

Drawings shall include at a minimum, a standard aeronautical 3-view orthographic projection arranged as described:

1. **Left** side view, in lower left, with nose pointed left.
2. **Top** view, above and aligned with the left side view, also with nose pointed left (wing-span break-view permitted).
3. **Front** view aligned to side view, located in the lower right (projection view non-standard movement as noted by projection view arrows in accordance with ANSI-Y14.5M 1994).

Dimensions Required

Drawing dimensions and tolerance shall be in English units, decimal notation accordance with ANSI-Y14.5M 1994 to an appropriate level of precision to account for construction tolerances (allowable variation from analyzed prediction to account for fabrication) (i.e. X.X = ± .1 in; X.XX = ± .03 in; X.XXX = ± .010 in).

The minimum required dimensions/tolerances are: Aircraft length, width, and height.

Summary Data Required

The drawing shall contain a summary table of pertinent data to include but not limited to:

1. Wingspan
2. **Wing Area**
3. **Aspect Ratio**
4. Empty weight
5. Battery(s) capacity
6. Motor make and model
7. Motor KV
8. Propeller manufacturer, diameter, and pitch
9. Servo manufacturer, model number and torque specification in ounce-inches for each servo used on the aircraft. Identify servo being used at each position on the aircraft.

Weight and Balance Information

The 2D drawing shall contain the following weight, balance, and stability information:

1. A clearly marked and labeled aircraft datum
2. A weight and balance table containing pertinent aircraft equipment. Each item listed must show its location from the aircraft datum in inches (the moment arm), the force, and resultant moment. See www.sae-aerodesign.com/go/downloads for additional information. The minimum list of pertinent equipment includes:
 - a. Motor
 - b. Battery(s)
 - c. Payload(s)
 - d. Electronics
3. Aircraft mean aerodynamic cord, stability margin and Center of Gravity (CG) information listed below must be clearly shown on drawing.
 - a. Aircraft mean aerodynamic cord
 - b. Stability margin for loaded CG and empty CG
 - c. Empty CG location (flightworthy)
 - d. Fully loaded CG (flightworthy, with payload, if applicable)

4.5 TECH DATA SHEET: PAYLOAD PREDICTION (REGULAR CLASS ONLY)

Regular Class must include a total payload prediction curve as part of the technical report. The graph represents an engineering estimate of the aircraft's lift performance based on density altitude.

1. Graph of payload weight shall be linearized over the relevant range.
2. The linear equation shall be in the form of:

$$y = mX + b$$

Y = Payload weight (lbs.)
 X = Density Altitude (feet)
 m = Slope of the linear line
 b = y-intercept.

3. Only one line and one equation may be presented on the graph. This curve may take into account predicted headwind for local conditions, rolling drag, inertia, motor and propeller performance, or any other factors that may affect take-off performance. All these factors are allowed components of the prediction curve, but only one curve will be allowed; multiple curves to account for varying headwind conditions will not be allowed.
4. The team must provide a brief explanation of how the line was generated in the body of the report. The section of the report containing this information must be noted on the payload prediction curve.
5. Graph axes shall be in English units, decimal notation.




Figure 4-1: Example Regular Class Payload Prediction Curve

4.6 TECH DATA SHEET: POWERED AUTONOMOUS DELIVERY AIRCRAFT (ADVANCED CLASS ONLY)

An additional 2D drawing must be provided as an Appendix for Powered Autonomous Delivery Aircraft (PADA). This 3-view must be ANSI B sized page (PDF) format (11 x 17 inches) and follow the same requirements as the primary aircraft 2D drawing.

1. Drawings shall identify the location of the loaded CG.
2. Teams shall provide a list of avionics and equipment.
3. Teams shall provide a prediction of landing accuracy for the PADA a landing zone. This shall be a histogram of the results of simulated landings by the PADA, binned in one-foot increments.
4. Teams must provide a standard deviation (in ft) assuming a mean of 0ft to be used in the calculation of their PADA Landing Bonus.




Figure 4-2: Example of Advanced Class Landing Distance Histogram

4.7 TECH DATA SHEET: AIR-SYSTEMS OPERATIONS PLAN

Advanced class must provide a sheet describing the systems operations plan and components as a block diagram. Show the breakdown of each system's functionality and interactions.

1. The diagram should represent the PA, PADA, Ground Station, and pilot(s)
2. Describe all communication methods between systems. Document any frequencies used and provide the make/model of any RF transmitters.

4.8 TECH DATA SHEET: AIRCRAFT PERFORMANCE PREDICTION (MICRO CLASS ONLY)

The Micro Class must include two figures describing the predicted flight performance of their aircraft between the start of takeoff and the beginning of the first turn. Both plots should be on the same page.

1. One figure must show the predicted ground distance vs time.
2. One figure must show the predicted altitude vs time.

5 TECHNICAL PRESENTATION

Like all professionals, engineers must possess a well-developed ability to synthesize issues and communicate effectively to diverse audiences. The technical presentation portion of the aero-design competition is designed to emphasize the value of an ability to deliver clear, concise, and effective oral presentations. Teams can obtain a maximum technical presentation score of fifty (50) points. The presentation score shall be comprised of scores based on the presenter's delivery technique and the judges' evaluation of technical content, empirical analysis, and visual aide.

5.1 TECHNICAL PRESENTATION REQUIREMENTS

1. Technical presentation shall last ten (10) minutes and be followed by a seven (7) minute "Question and Answer" (Q&A) period.
2. Technical presentation shall be delivered in English.
3. Technical presentation shall address, but are not limited to, trade studies performed, design challenges, and manufacturing techniques.
4. Technical presentation is limited to student team members only. Non-team member pilot or Faculty Advisors can attend the technical presentation but are prohibited from participating in the setup, delivery, and/or the Q&A.
5. Assistance in the use of visual aids is advisable; Film clips, if used, may not exceed one-minute total duration; Film clips may not be accompanied by recorded narration.
6. During the Q&A section, the teams shall display a single page marketing/promotion piece to further detail aircraft's feature, capabilities, and unique design attributes.

5.2 TECHNICAL PRESENTATION PROCESS AND PROCEDURES

Each presentation room shall have a lead judge with the responsibility to ensure compliance with competition rules and schedule. The lead judge will identify a timekeeper.

1. With agreement from the speaker, the timekeeper will give the speaker a one (1) minute warning prior to the ten (10) minute limit.
2. If the team exceeds the ten (10) minute limit, the team will be assessed a five (5) point penalty for going over the time limit.
3. The presentation shall be stopped at the eleven (11) minute mark.
4. A team shall have seven (7) minutes for Q&A immediately following the presentation. Questions may be asked by any judge on the panel.
5. Any time remaining or exceeding the ten (10) minutes shall be added to or subtracted from the seven (7) minute Q&A.
6. Presentation Time Breakdown:

Time (Minutes)	Description
2	Setup presentation
10	Perform Technical Presentation
7	Questions & Answers
1	Close down presentation

6 REQUIREMENTS CHECK & SAFETY AND AIRWORTHINESS INSPECTION

Requirements Check & Safety and Airworthiness Inspection of all aircraft will be conducted using the published checklists for each class for the current year. The checklists can be found at: www.saeaerodesign.com/go/downloads

Safety and Airworthiness Inspection is the process of checking each aircraft for any issues or problems that could cause a safety problem in flight or on the ground.

Requirements Check is the process of checking all aircraft for:

- Compliance with all General aircraft requirements.
- Compliance with all Class-specific requirements.
- The aircraft presented matches the design submitted by the team.

All aircraft must pass the Requirements Check & Safety and Airworthiness to compete. **Per the Statement of Compliance, teams are required to present a fully completed Requirements Check & Safety and Airworthiness Inspection for their aircraft that is signed by the Faculty Advisor or Team Captain.** Teams cannot begin the inspection process without meeting this requirement. Inspectors at the event will confirm that the team has fully inspected their aircraft.

Aero Design is changing how General Aircraft and Class Requirements are checked for compliance. Inspectors will be given a list of five to seven requirements to spot check, instead of checking all items. These will be randomly chosen just before the event. Even though items are being spot checked, teams must be in compliance with all items at all times.

New for 2023 are penalties for failing any part of the spot Requirements Check for General Aircraft requirements and Class requirements. See section 6.6 for penalty details.

6.1 AIRCRAFT CONFORMANCE TO 2D DRAWING

During Technical Inspection, the aircraft will be inspected and measured for conformance to the 2D drawing presented in the Design Report.

1. At a minimum, aircraft length, wingspan and height dimensions will be measured and compared to the 2D drawing.
2. Aircraft will have the actual empty CG compared to the empty CG presented in the design report 2D drawing.

6.2 DEVIATIONS FROM 2D DRAWING

Any deviation in construction of the aircraft from the submitted 2D drawing, after submission of the Design Report, must be reported in writing. **For Advanced and Regular Class aircraft, there is no need to report deviations in the length (L), width (W), and height (H) of the aircraft, if the following is satisfied, where dimensions are in inches:**

$$|L_{actual} - L_{drawing}| + |W_{actual} - W_{drawing}| + |H_{actual} - H_{drawing}| \leq 3 \text{ inches}$$

6.3 SAFETY AND AIRWORTHINESS OF AIRCRAFT

Safety and Airworthiness Inspection will also be used to assess the general safety and airworthiness aspects of each aircraft by seeking any problems that could cause an aircraft to depart controlled flight. This assessment includes, but is not limited to:

1. Unintentional wing warps
2. Control surface alignment
3. Correct control surface response to radio transmitter inputs
4. Linkage problems
5. Structural and mechanical soundness of aircraft

6.4 INSPECTION OF SPARE AIRCRAFT AND SPARE AIRCRAFT COMPONENTS

1. All spare aircraft and spare aircraft components (wings, fuselages and tail surfaces) must be presented for inspection.
2. Teams may submit up to two (2) complete aircraft at Inspection on Friday.
3. Additional spare aircraft and parts beyond two (2) sets may be submitted for inspection during the event on Saturday and Sunday.

6.5 AIRCRAFT MUST MAINTAIN COMPLIANCE THROUGHOUT THE COMPETITION.

1. All aircraft must meet all Requirements Checks & Safety and Airworthiness requirements throughout the competition.
2. Any official may request that an aircraft be re-inspected if a general, class configuration, or safety/airworthiness requirement problem is seen on an aircraft at any time during the event.
3. This includes any errors or omissions made by officials during inspection.

6.6 REQUIREMENTS CHECK & SAFETY AND AIRWORTHINESS INSPECTION PENALTIES

1. If a team fails the spot check process for any of the General Aircraft requirements or Class requirements, there will be a point penalty for each item failed. The aircraft must be brought into compliance to compete.
2. Aero Design reserves the right to assess the point penalty on any requirement item found during inspection, even if the item is not on the spot check list.
3. Any Requirements Check failure involving penalty points will be confirmed by a Rules Committee member before points are assessed.
4. No additional penalty points will be assessed for a team's second aircraft that has the same requirements failure as the first aircraft.
5. If a Requirements Check item failure is found on an aircraft after inspection or during flight rounds, the point penalty will be applied, any flight score earned while the aircraft was non-compliant will be zeroed, and the aircraft will have to be brought into compliance before flying again.
6. There are no penalty points for failing any Safety or Airworthiness item. However, the team must correct any failures before the aircraft is allowed to compete. Flight points earned while the aircraft was not in compliance with Safety and Airworthiness requirements may be subject to being zeroed.

7 REGULAR CLASS DESIGN REQUIREMENTS

The objective of Regular Class is to design an aircraft that can lift as much weight as required while maximizing wingspan. Payload will consist of Regular Boxed Cargo, represented by payload weights, which must be carried on each flight. Accurately predicting the lifting capacity of the aircraft is an important part of the aircraft design.

7.1 AIRCRAFT DIMENSION REQUIREMENT

Regular Class aircraft are limited to a minimum planform wingspan of 120 inches.

Regular Class aircraft are limited to a maximum planform wingspan of 216 inches. When off the flight line, teams will be required to remove outer wing sections for easy transport.

Wings with small cord extensions added to gain span are not allowed. There can be no cord steps or discontinuity in the projected wing drawing. Minimum wingtip cord is 4 inches.

No individual part may measure more than 48 inches along any primary axis as measured in the flight configuration aircraft body frame. An individual part is any portion of the airframe that can be completely separated from the rest of the airframe. Components that are permanently attached to each other (ie bonded) are considered to be members of the same part.

7.2 MATERIAL AND EQUIPMENT RESTRICTIONS FOR REGULAR CLASS

Fiber-Reinforced Plastic (FRP)

The use of Fiber-Reinforced Plastic (FRP) is prohibited on all parts of the aircraft. Fiber-Reinforced Plastic includes duct tape. Exceptions to this rule include: commercially available FRP motor mount, propeller, landing gear and control linkage components. Exploration of alternative materials is encouraged.

Rubber bands

Elastic material such as rubber bands shall not be used to retain the wing or payloads to the fuselage.

Stability Assistance

All types of gyroscopic or other stability assistance are prohibited.

7.3 AIRCRAFT SYSTEM REQUIREMENTS

Electric Motor Requirements

The aircraft shall be propelled by a single electric motor (no multiple motors). There are no restrictions on the make or model of the electric motor.

Gear boxes, Drives, and Shafts

Gearboxes, belt drive systems, and propeller shaft extensions are allowed if a one-to-one propeller to motor RPM is maintained. The prop(s) must rotate at motor RPM.

Aircraft Propulsion System Battery

Regular Class aircraft must be powered by a commercially available 6 cell (22.2volt) Lithium-Polymer battery pack. Minimum requirements: 3000 mAh, 25c.

Power Limiter

All Regular Class aircraft must use a 2018 V2 or newer version 750-watt power limiter from the official supplier (Neumotors.com) as described in Section 2.19. If you have a 1000-watt limiter, you can send them back to be changed to 750-watts.

Receiver System Battery and Switch

A separate battery or separate BEC is **required** for the receiver system. If using a battery, it must have enough capacity to safely drive all the servos in the aircraft, taking into consideration the number of servos and maximum current draw. The aircraft receiver system must be able to operate without the arming plug installed.

1. The receiver system battery pack must have a minimum capacity of 1000 mAh.
2. The battery pack must be a LiPo or LiFE type battery.
3. Battery voltage regulators are allowed.
4. The receiver system must be controlled by a clearly visible and properly mounted on/off switch mounted to the exterior of the aircraft, located at least 12" from the propeller.

7.4 PAYLOAD REQUIREMENTS

Types of Cargo

Regular Class payload shall consist of Regular Boxed Cargo, which must be carried internally to the aircraft. Payload attachment must be designed for ease of access. Reference Section 7.5 for demonstration details.

Cargo Bay Requirements

Regular Class aircraft shall have a single fully enclosed Cargo Bay for carrying Regular Boxed Cargo with the following additional requirements:

1. The Cargo Bay shall fully enclose the Regular Boxed Cargo. Regular Boxed Cargo may not be exposed to airstream at any point in flight.
2. The Cargo Bay has no restriction on size or shape.
3. Only one Cargo Bay is allowed in a Regular Class aircraft.

Regular Boxed Cargo Support Requirements

Regular Boxed Cargo shall consist of a support assembly and payload plates with the following additional requirements:

1. There is no required configuration for the payload plates, other than as defined by Section 2.10 and 2.11.
2. Teams must provide their own payload plates.
3. Tape, Velcro, rubber bands, container systems and friction systems alone may not be used to retain the support assembly and/or payload plates.

7.5 REGULAR CLASS PAYLOAD UNLOADING

To complete a successful flight for score, the post flight activities of unloading Regular Boxed Cargo must be accomplished within one (1) minute. This demonstration will be performed at the weigh station after the completion of each successful flight.

This activity is timed and shall be performed by no more than two (2) members of the team.

The demonstration will start with all Regular Boxed Cargo loaded, secured, and the aircraft configuration unchanged from the most recent successful flight.

Only Regular Boxed Cargo successfully unloaded from the aircraft within the time limit will be weighed and recorded for scoring that flight attempt.

7.6 REGULAR CLASS SCORING

To participate in the flight portion of the competition, each team is required to have submitted AND received a score for their Design Report and Oral Presentation.

The team's Final Flight Score is the sum of the top three (3) flight scores the team achieves during the competition (FS_1 , FS_2 , and FS_3) and the Wingspan Score.

Scoring Equation:

$$FFS = \text{Final Flight Score} = FS_1 + FS_2 + FS_3 + WS$$

Where:

$$FS = \text{Flight Score} = \frac{W_{\text{Payload}}}{2} + PPB$$

$$PPB = \text{Payload Prediction Bonus} = \text{MAX} \left(5 - (W_{\text{payload}} - P)^2, 0 \right)$$

$$WS = \text{Wingspan Score} = 2^{\left(1 + \frac{b}{5}\right)}$$

$$W_{\text{Payload}} = \text{Regular Boxed Cargo Weight (lbs)}$$

$$b = \text{Aircraft Wingspan (ft)}$$

$$P = \text{Predicted Payload}$$

The predicted payload, P , is determined from the payload prediction curve the teams provide in the Technical Data Sheet (Section 4.5) and the density altitude measured at the event.

The Payload Prediction Bonus will be calculated for each flight. All Payload Prediction Bonus (PPB) less than zero (0) will default to zero (0).

Wingspan Score will only be calculated after a team has a successful flight.

Penalty Points

Any penalty points assessed during the competition are now deducted from a team's overall score.

8 ADVANCED CLASS DESIGN REQUIREMENTS

The objective of Advanced Class is to design a suite of systems that can support the fight against wildfires through the delivery of water and parts for a ground vehicle. This class is focused on mission success through understanding of diverse requirements, system-level engineering, and robust execution.

8.1 VIDEO DOCUMENTATION OF PROVEN OPERATIONAL ABILITY FOR ADVANCED CLASS

All Advanced Class teams are required to bring a video documenting the proven operational ability of their Advanced Class aircraft to Inspection. The hard deadline for video submission is 8AM Saturday morning of the competition weekend.

1. The video must show the following activities accomplished successfully with their competition aircraft: A take-off, a successful release of a PADA, a PADA in stable flight for at least 10 seconds, and a landing of the Primary Aircraft (PA) without damage to the PA. A successful release of the PADA means that the PADA is in a flyable configuration after release.
2. The video will be reviewed by SAE officials in the Inspection area.
3. Advanced Class aircraft will not be inspected or allowed to compete without the video documentation of proven operational ability.
4. Teams must provide a device to play the video for the officials at a screen size that allows the officials to clearly see both aircraft.
5. Videos should be no more than 1.5 minutes in length. Edited video will be accepted if the video is of the same flight.

8.2 AIRCRAFT DIMENSION REQUIREMENT

Advanced Class aircraft are limited to a maximum planform wingspan of **120 inches**.

8.3 AIRCRAFT SYSTEM REQUIREMENTS

Electric Motor Requirements

The Primary Aircraft shall be propelled by one or more electric motors. There are no restrictions on the make or model of the electric motor.

Gear boxes, Drives, and Shafts

Gearboxes, belt drive systems, and propeller shaft extensions are allowed.

Aircraft Propulsion System Battery

Advanced Class aircraft must be powered by a commercially available 6 cell (22.2volt) Lithium-Polymer battery pack. Minimum requirements: 3000 mAh, 25c.

Power Limiter

All Advanced Class Primary Aircraft shall use a single 2018 or newer version 750-watt power limiter from the official supplier (Neumotors.com) as described in Section 2.19.

8.4 RECEIVER SYSTEM BATTERY

A separate battery or separate BEC is **required** for the radio system. If using a battery, it must have enough capacity to safely drive all the servos in the aircraft, taking into consideration the number of servos and maximum current draw. The aircraft receiver system must be able to operate without the arming plug installed.

1. The radio system must use a battery pack with a minimum capacity of 1000 mAh.
2. The battery pack must be a LiPo or LiFE type battery.
3. Battery voltage regulators are allowed.
4. The battery pack must be controlled by a clearly visible and properly mounted on/off switch on the external surface of the PA, located at least 12" from the prop.

8.5 RUBBER BANDS

Elastic material such as rubber bands shall not be used to retain the wing to the fuselage.

8.6 PRIMARY AIRCRAFT STATIC PAYLOAD REQUIREMENTS

Water Storage Container Requirements

Each team shall provide at least two (2) storage containers. At least one (1) main storage container to hold all the water carried as Static Payload by the primary aircraft. At least one (1) destination storage container to hold all the water delivered by the Ground Transport Vehicle (GTV).

1. After each successful mission, the Static Payload will be impounded into the team's main water storage container(s). Teams will not have access to this water until the GTV demonstration.
2. Containers must be clearly marked with team name and number.
3. Containers should have a sealable lid to prevent spilling.
4. Any evaporation, leakage, or other loss of water is the team's responsibility.

Static Payload Requirements

1. The primary aircraft shall carry a static payload of water.
2. Static payload bay(s) shall have no restriction on size or shape.
3. Teams must be able to unload Static Payload into the main water storage container at the weigh station after the flight in three (3) minutes or less.
4. Any water not unloaded during the time limit shall not be counted for score.

8.7 POWERED AUTONOMOUS DELIVERY AIRCRAFT (PADA) REQUIREMENTS

Teams are responsible for delivering a Ground Transport Vehicle (GTV) safely to the ground through a powered and autonomously guided aircraft. The following requirements apply to the PADA:

1. Total weight of each fully loaded PADA must be not more than 16.0 oz
2. PADA must be a fixed wing aircraft and is subject to requirements in Section 1 and 2.
3. The team may have multiple PADAs, but only one (1) can be mounted and flown on the primary aircraft per flight.

4. The PADA must have a propulsion system, consisting of at least a propeller, motor, battery, and speed controller.
5. The PADA must use a separate battery pack or battery eliminator circuit (BEC) to power the receiver. The red power wire from the ESC must not be connected to the receiver.
6. The center of gravity must be clearly marked on each PADA according to Section 2.3.
7. Payload may be carried internally or externally. Any internal payload bay(s) shall have no restriction on size or shape.
8. The PADA shall be considered a structural part of the Primary Aircraft prior to the intentional release and separation towards the target landing zone. The entirety of the PADA is considered as payload after release. Section 3.5 will be observed if the PADA loses parts while attached to the Primary Aircraft. Structural components will result in a disqualification of the flight attempt. Non-structural components will result in a 25% penalty.
9. Powered taxi of the PADA is prohibited.

8.8 LANDING ZONES

The PADA will be required to land in a preselected landing zone. Teams must demonstrate their ability to successfully land in the static zone before attempting landings in a random zone.

Static Zone

1. One (1) Zone with a diameter of 30ft will be placed on the far side of the runway.
2. The GPS coordinates for this zone will be provided to teams and will remain in place throughout the duration of the competition.

Random Zone

1. There will be at least three (3) zones, located on the far side of the runway.
2. Each zone will have a diameter of 30 ft, with the center marked by a solid-colored sign of at least 24" in diameter laying flat on the ground.
3. The location of each zone may be changed at any point during the competition.
4. Teams will not be allowed access to the field to obtain GPS coordinates at any time during the competition.
5. Only PADAs that land in the target zone selected for that flight attempt will be counted for score.

8.9 GROUND TRANSPORT VEHICLE (GTV) REQUIREMENTS

The payload for the PADA shall consist of components for a ground vehicle, which teams shall assemble and demonstrate at the conclusion of all flight activities. The following requirements apply to the GTV:

1. Other than the water payload and transmitter (if used), the entire GTV system, and everything necessary to construct, operate and maintain it, must be delivered as payload via PADA flights. This includes but is not limited to wheels, batteries, motors, the receiver, fasteners, tools, tape, water funnel, etc.

2. After each successful PADA landing in a Random Zone only, any desired GTV components shall be unloaded and placed in an impound box, where they will remain until the GTV demonstration.
3. Teams shall provide their own impound box which shall be a rectangular prism with a removable lid and be marked with the team's name and number.
4. The payload for the GTV during the demonstration shall be water. The water payload must be drawn from the team's main water storage container filled by the Primary Aircraft. The water shall be delivered to the destination water storage container.

8.10 GYROSCOPIC AND OTHER STABILITY AUGMENTATION

Gyroscopic assist or other forms of stability augmentation are allowed in Advanced Class.

8.11 AUTONOMOUS FLIGHT

Autonomous flight systems that cause the Primary Aircraft to navigate without direct pilot control input are prohibited. Autonomous flight for the PADA is required, subject to the following rules:

1. Teams must provide at least one fully functional PADA that meets all requirements herein.
2. In addition to the motor, the PADA shall have an active navigation system, controlling at least 2 degrees of freedom, that guides the PADA toward the target landing zone following its release from the Primary Aircraft.
3. Teams must have a manual override for control over the PADA through a dedicated secondary transmitter. This shall be a switch on that transmitter to select between autonomous and manual flight modes.
4. The team must have a dedicated pilot for the PADA who will use the secondary transmitter if manual override is used. This pilot will stand with the Primary Aircraft pilot near the Airboss or designated representative.
5. Manual override may be used at the discretion of the team. Any use of the manual override shall be considered an unsuccessful PADA flight.
6. If the PADA is flying in an unsafe manner, the Airboss may order grounding of the PADA as per Section 3.11.5. The PADA flight shall be considered unsuccessful.

8.12 FREQUENCY REQUEST PROCEDURE

Advanced Class teams will need to fill out Frequency Request form in Appendix C to request frequency assignment for DAS, FPV, or other RF links. Teams must submit the document via email by **February 15th, 2023**. SAE rules committee will work with teams to deconflict if multiple teams request similar frequencies.

8.13 DATA ACQUISITION SYSTEM (DAS)

Advanced Class Primary Aircraft must have a Data Acquisition System (DAS) that shall record altitude and be used by the team to locate the appropriate target landing zone. All communication between the payload specialist and any pilot must be in English.

1. Using a ground receiver station, the team must display the real-time altitude of the aircraft to the Payload Specialist and the flight judge in at least 1.0 inch text.
2. Team must automatically record, and immediately display in at least 1.0 inch text, the altitude (ft) at the moment of release for the PADA. The indicator must remain visible for the remaining duration of the flight.
3. The DAS recording must be performed on the ground station and must support play back for review on demand.
4. Altitude must be measured in feet with display precision of at least one (1) ft. and an accuracy error of less than ten (10) ft.
5. DAS system must use a discrete and removable Red arming plug to apply power to the DAS system. This arming plug is subject to the requirements in Section 2.20. One Red arming plug can be used for both DAS and FPV.
6. DAS equipment may also have a reset switch, if desired. If a manual reset switch is used, it must be located externally at least 12 inches behind the propeller in the longitudinal direction. A wireless DAS reset system is allowed.
7. DAS systems shall not use the same 2.4 GHz channel as the flight control system, unless the telemetry being used is part of the radio control system being used. A DAS built into the radio control system must meet all DAS rules requirements.

8.14 DAS FAILURES

Any DAS failure during the flight attempt is considered a missed flight attempt and receives zero (0) points.

Example: A team has flown four (4) times successfully and on the 5th attempt the Primary Aircraft takes-off successfully, makes a successful release, but the DAS altitude reading malfunctions. The flight attempt will NOT be considered a qualified flight and the team will receive zero (0) credit for PADA or static payload for flight 5.

8.15 FIRST PERSON VIEW SYSTEM (FPV)

FPV is not required for Advanced Class. For teams that wish to use an FPV system for operational reasons, the following conditions apply:

1. Teams will be required to follow the frequency request process to be assigned a frequency for their FPV systems. Frequency control procedures will be in place at the event to prevent conflicts.
2. The primary pilot must fly visually only (no FPV goggles or ground station reference).
3. FPV systems CANNOT use the same frequency as the flight control system. Use of 2.4 GHz for FPV video is prohibited.
4. The FPV system must use a discrete and removable Red arming plug to apply power to the FPV system. This arming plug is subject to the requirements in Section 2.20. One Red arming plug can be used for both DAS and FPV.

8.16 PAYLOAD SPECIALIST

The Payload Specialist is responsible for releasing the PADA from the Primary Aircraft.

1. The Payload Specialist must be a single team member. The Payload Specialist should not count on having a line-of-sight view to the aircraft or target(s).
2. Neither the primary aircraft pilot nor the PADA pilot may have access to or activate any PADA release, and the release cannot be connected to the pilot's R/C transmitters in any way.
3. The PADA release must be manually activated by the Payload Specialist or by an automatic release system that is part of the Primary Aircraft electronics.
4. If an automatic release system is used, it must have a manual override controlled by the Payload Specialist.
5. Teams may activate the payload release system using a second 2.4 GHz radio system or some other method based on their DAS or telemetry system.

8.17 POWERED AUTONOMOUS DELIVERY AIRCRAFT RELEASE PROCEDURES

1. Release of the PADA must be at least 200 feet away from the center of the runway, measured parallel to the runway.
2. Teams must release the PADA at an altitude of no greater than 50 ft.
3. Teams have as many passes as needed, so long as the PADA is released within 4 minutes of throttle-up, lands within 5 minutes of throttle-up, and the Primary Aircraft comes in to land as soon as the PADA is released.
4. A single PADA shall be successfully launched during each flight attempt. Failure to launch a PADA successfully and intentionally shall disqualify the entire flight attempt. A successful launch is defined as:
 - Being within 4 minutes of primary aircraft throttle-up
 - Complying with Section 8.17.1 and 8.17.2 as shown in Figure 8-1.
 - The PADA must attain stable flight after release.




Figure 8-1 – Notional PADA Release Diagram. Not to scale.

8.18 GROUND TRANSPORT VEHICLE DEMONSTRATION EVENT PROCEDURE

At the conclusion of all flight activities, before the award ceremony, teams shall have 8 minutes to demonstrate their GTV's ability to transport water in the following manner:

1. Each team will be set up in a designated area of the runway with sufficient separation from other teams to avoid interference.
2. On one side of the demonstration zone will be the unassembled GTV in the impound box and the team's main water storage container(s). Stationed on the other side of

- the zone (approx. 30 feet away) shall be the team's empty destination water storage container(s). Containers shall be positioned approximately as shown in Figure 8-2.
3. No more than three (3) team members may take part in the assembly and demonstration, including the manual driver. Teams may split personnel between the start and destination sides of the area however they choose, but no team member may switch sides during the demonstration.
 4. When the demonstration begins, the team shall assemble their GTV, load it with water from the main water storage container and navigate it to the other side of the runway. Once the GTV has completely passed the finish line, the team member(s) on the other side of the runway shall unload the water into the destination storage container(s). Only water that has crossed the finish line with the GTV will be counted for score.
 5. Teams may handle the water storage containers, but neither the main nor destination water storage containers may be moved during the demonstration.
 6. Multiple trips across the demonstration zone are allowed.
 7. Team members on the starting side may only refill the GTV after it has completely left the demonstration zone.
 8. The GTV may be autonomous or manually controlled. If the team controls the GTV via a transmitter when it is within the demonstration zone, the GTV shall be considered manually controlled for the entirety of the demonstration. Teams may touch, control, or manipulate an autonomous GTV when it is outside of the demonstration zone and the GTV shall still be considered autonomous. Touching the GTV while it is within the demonstration zone is prohibited under all circumstances.
 9. Obstacles will be placed in the demonstration zone approximately as shown in Figure 8-2. The obstacles may be up to 3 inches in height.
 10. Only the water successfully delivered by the GTV within the time limit shall be measured for score.




Figure 8-2: Notional Diagram of GTV Demonstration Event. Not to Scale.

8.19 ADVANCE CLASS SCORING

To participate in the flight portion of the competition, each team is required to have submitted AND received a score for both Design Report and Oral Presentation.

The team's Final Flight Score is the sum of the top three (3) flight scores the team achieves during the competition (FS_1 , FS_2 , and FS_3) and the GTV event score. Teams are given points based on the amount of water the primary aircraft successfully carries each flight and a flat score every time a PADA successfully lands in the designated landing zone, with a bonus for distance to the center derived from the team's predictions. Finally, the teams who delivered enough parts via PADAs to assemble a working GTV will have the opportunity to score points by transporting the water carried previously by the primary aircraft in a demonstration event.

Scoring Equation:

$$\text{Final Flight Score} = FS_1 + FS_2 + FS_3 + GTV$$

Where:

$$FS = \text{Flight Score} = W_{\text{Payload}} + 8 * (Z_{\text{PADA}} + B_{\text{PADA}})$$

$$GTV = \text{Ground Score} = \frac{A_{\text{GTV}} * W_{\text{delivered}}}{4}$$

$$B_{\text{PADA}} = \text{PADA Landing Bonus}^* = 5 * \left(\frac{1}{\sigma\sqrt{2\pi}} e^{-\frac{d^2}{2\sigma^2}} \right)$$

**Note, this is the normal probability density function with mean of 0*

$W_{\text{payload}} = \text{Water (lbs) Successfully Flown}$

$W_{\text{delivered}} = \text{Total Water (lbs) Delivered by GTV During Demonstration}$

$A_{\text{GTV}} = \text{GTV Autonomy Multiplier: 2 if autonomous, 1 if manual}$

$Z_{\text{PADA}} = \text{PADA Zone Multiplier: 2 for random, 1 for static}$

$d = \text{Distance of PADA to center of landing zone, rounded down to nearest ft}$

$\sigma = \text{Team supplied Standard Deviation from TDS (ft)}$

Penalty Points

Any penalty points assessed during the competition are now deducted from a team's overall score.

9 MICRO CLASS DESIGN REQUIREMENTS

The objective of the Micro Class is to challenge engineering students to design a small, light-weight, all electric aircraft to overcome various conflicting design and performance requirements such as short take-off, max-speed, external payload carriage, internal payload carriage, and rapid unloading of the payloads.

9.1 AIRCRAFT DIMENSION REQUIREMENTS

Micro Class aircraft are limited to a maximum planform wingspan of 36 inches

9.2 AIRCRAFT SYSTEMS REQUIREMENTS

Propulsion Requirements

Micro Class aircraft are restricted to electric motor propulsion only.

Propeller and Gearbox

Gearboxes on a Micro Class aircraft where the propeller RPM differs from the motor RPM are allowed. Multiple motors, multiple propellers, propeller shrouds, and ducted fans are allowed in Micro Class.

Aircraft Propulsion System Battery

Micro Class aircraft must use Lithium Polymer batteries. Micro class batteries are allowed a maximum of 4 cells.

Gyroscopic Assist Allowed

Gyroscopic assist and other forms of stability augmentation are allowed in Micro Class.

Power Limiter

All Micro Class aircraft must use a 2021 or newer version 450-watt power limiter from the official supplier (Neumotors.com) as described in Section 2.19.

9.3 PAYLOAD REQUIREMENTS

Types of Cargo

Micro Class payload shall consist of two types; (1) metal payload plates and (2) delivery boxes. The metal payload plates shall be carried internally to the aircraft in a cargo bay.

Cargo Bay Requirements

Micro Class aircraft shall have a single Cargo Bay for carrying payload plates with the following additional requirements:

1. The Cargo Bay shall fully enclose the payload plates.
2. The Cargo Bay has no restriction on size or shape.
3. Only one Cargo Bay is allowed in a Micro Class aircraft.

Payload Plate Support Requirements

Payload Plates shall be secured with a support assembly subject to the following additional requirements:

1. There is no required configuration for the payload plates, other than as defined by Section 2.10 and 2.11.
2. Teams must provide their own Payload Plates.
3. Tape, Velcro, rubber bands, container systems and friction systems alone may not be used to retain the support assembly and/or Payload Plates.

Delivery Box Definition

Two sizes of delivery boxes (Large and Small) are utilized in Micro Class.

1. Both boxes are rectangular prisms with specifications consistent with the table:

Type	Length (in)	Width (in)	Height (in)	Wt (oz)
Large	12±0.25	12±0.25	2±0.25	5.5±0.5
Small	6±0.25	6±0.25	4±0.25	2.5±0.5

2. Delivery boxes will be **supplied by SAE**.
3. Teams must attempt to carry at least one (1) box
4. There is no configuration requirement for the Delivery Boxes.
5. Boxes may not be modified by the team. No holes or mounting hardware are permitted on the boxes.
6. The delivery boxes must remain intact throughout the duration of the flight to receive full score. Damaged boxes shall count for 50% score. Destroyed boxes shall be disqualified.

Intact: Box geometry and dimensions remain unchanged throughout the duration of the flight.

Damaged: Box Interior of the box is not exposed (no punctures, tears etc.) AND All box dimension deviates from specification by less than 0.5"

Destroyed: Interior of the box is exposed by a rip/tear/puncture (box no longer airtight) OR Any box dimension deviates from specification by more than 0.5"

9.4 PAYLOAD UNLOADING

To complete a successful flight for score, the post flight activities of unloading delivery box(es) and unloading static payload must be accomplished within one (1) minute. This demonstration will be performed at the weigh station after the completion of each successful flight.

The demonstration will start with all Delivery Box(es) and Payload Plates loaded, secured, and the aircraft configuration unchanged from the most recent successful flight.

This is a timed activity and shall be performed by no more than two (2) members of the team.

- Any Payload Plate(s) successfully unloaded from the aircraft will be weighed and recorded for scoring that flight attempt.

- Any Delivery Box(es) successfully unloaded from the aircraft will be recorded for scoring that flight attempt.
- Any Delivery Box(es) or Payload Plate(s) that **fails** to be unloaded within one (1) minute will not be used in the scoring equation.

9.5 MICRO CLASS AIRCRAFT LAUNCH

The Micro Class aircraft must accomplish a take-off from a designated 4-foot by 8-foot take-off platform that is elevated at a minimum of 24-inches above the ground. The take-off area will be approximately level.

- The pilot and one (1) team member may be at the take-off area.
- The aircraft must be only held and released by one (1) team member. Release of the aircraft by the pilot is prohibited.
- The weight of the aircraft must be supported by the landing gear while on the platform. All landing gear, and aircraft ground contact points must be in contact with the surface of the platform. The rear of the aircraft may overhang the platform.

9.6 MISSION REQUIREMENTS

Aircraft Take-off and Circuit

Micro Class Take-off is defined as the point at which the aircraft moves forward under its own power. Micro Class aircraft are required to perform the following operations, referenced in Figure 9-1:

1. Take-off as described in Section 9.5. The Flight Timer is started at the moment of forward aircraft movement.
2. Remain airborne and fly past a designated turn point 300-ft from the take-off before turning approximately 180-degrees in heading. The Flight Timer is stopped when the aircraft is indicated to have crossed the designated turn point.
3. Fly past a second designated turn point, turning 180 degrees in heading.
4. Land within the 200-ft designated landing zone. Micro Class aircraft must be prepared to land on either a paved or unpaved landing zone.
5. Take-off direction will be determined by the Air Boss, and normally selected to face into the wind.




Figure 9-1 – Notional Micro-Class Flight Circuit

9.7 MICRO CLASS FLIGHT SCORING

To participate in the flight portion of the competition, each team is required to have submitted AND received a score for both Design Report and Oral Presentation.

The team's Final Flight Score is the sum of the top three (3) flight scores the team achieves during the competition (FS_1 , FS_2 , and FS_3).

Scoring Equation:

$$\text{Final Flight Score} = FSS = FS_1 + FS_2 + FS_3$$

Where:

$$\text{Flight Score} = FS = 80 * \frac{\sqrt{W_{\text{Payload}} * \text{Bonus}}}{T_{\text{Flight}}}$$

$$\text{Bonus} = 0.5 + (1.0 * N_{\text{Large}}) + (0.4 * N_{\text{Small}})$$

N_{Large} = Number of Large Boxes Flown

N_{Small} = Number of Small Boxes Flown

W_{Payload} = Payload Plate Weight (lbs)

T_{Flight} = Flight Time from Take – off to First Turn (s)

Penalty Points:

Any penalty points assessed during the competition will be deducted from the team's overall score.

APPENDIX A - STATEMENT OF COMPLIANCE

Certification of Qualification

Team Name	_____	Team Number	_____
School	_____		
Faculty Advisor	_____		
Faculty Advisor's Email	_____		

Statement of Compliance

As faculty Adviser:

_____ (Initial) I certify that the registered team members are enrolled in collegiate courses.

_____ (Initial) I certify that this team has designed and constructed the radio-controlled aircraft in the past nine (9) months with the intention to use this aircraft in the **2023** SAE Aero Design competition, without direct assistance from professional engineers, R/C model experts, and/or related professionals.

_____ (Initial) I certify that this year's Design Report has original content written by members of this year's team.

_____ (Initial) I certify that all reused content have been properly referenced and is in compliance with the University's plagiarism and reuse policies.

_____ (Initial) I certify that the team has used the Aero Design inspection checklist to inspect their aircraft before arrival at Technical Inspection and that the team will present this completed checklist, signed by the Faculty Advisor or Team Captain, to the inspectors before Technical Inspection begins.

Signature of Faculty Advisor

Date

Signature of Team Captain

Date

Note: A copy of this statement needs to be included in your Design Report as page 2 (Reference Section 4.3)

APPENDIX B - APPEALS

Team Name	
Team Captain	
Collateral Points	<p><i>All appeals will require the team to post twenty-five (25) points as collateral. If the appeal is successful and the action is reversed, the team will not forfeit the twenty-five (25) collateral points. If the appeal is overruled, the team will forfeit the twenty-five (25) collateral points</i></p> <p>Collateral Points: <input type="text" value="25"/></p> <p>Sign if Agree: _____</p>
Reason for this Appeal	
Rule Reference	<p><i>List the section(s) in the official rule that is (are) in conflict with the action(s) taken by competition official</i></p> <p>Section: _____ Section: _____</p> <p>Section: _____ Section: _____</p>
Desire outcome	

APPENDIX C – DAS, FPV, RADIO FREQUENCY REQUEST FORM

Advanced Class teams must fill out and submit this document to Glennsaefreq@gmail.com

Frequencies will be assigned as a group number in order of receipt, and teams will receive confirmation via email. Conflicts will be resolved via follow-up communication with teams.

If the transmitter is spread-spectrum, please indicate and restrict each choice to a three whole-number range.

All teams should be prepared to make adjustments at the competition.

COMPETITION (EAST/WEST)	
TEAM NUMBER	
SCHOOL NAME	
TEAM NAME	

	MAKE / MODEL
PRIMARY AIRCRAFT RC CONTROLLER	
PRIMARY AIRCRAFT RC RECEIVER	
PADA OVERRIDE RC CONTROLLER	
PADA OVERRIDE RC RECEIVER	

SYSTEM	TRANSMITTER MANUFACTURER AND MODEL	FREQUENCY CHOICE			WATTAGE
		FIRST	SECOND	THIRD	
FPV					
DAS					
OTHER					